

ChargePost



2

CHARGING POINTS enable simultaneous charging of two e-vehicles.

24/7

OPERATION THANKS to intelligent buffer storage.

Up to 201 kWh

BATTERY CAPACITY.

1.3x1.5x2.4 m

COMPACT SIZE for maximum flexibility during assembly.

75 inch

advertising displays for the placement of **ULTRA-HD** advertising content.

5 min

of charging for more than a **100 KM DRIVE.**

10 inch

sunlight-optimized **TOUCHSCREEN** ensures optimum readability.

Up to 300 kW

or **2x150 kW** super-fast charging power.

ChargePost

Technical Data

Product variants		ChargePost
Electronics	Charging power Output voltage DC Max. charge current (output)	Up to 300 kW or 2x150 kW 150 – 920 VDC Max. 400 A
Battery	Gross capacity Cell technology	143.6 kWh or 201 kWh Lithium-ion
Installations	Operation parallel to the grid Secured charging cable	Yes Yes, fixed installations with connection terminals
Grid connection	Power supply form Power supply system Power supply frequency Input voltage AC Input power EMC	3-phase + N + PE TN-S 50 Hz 400 V (+/- 10%) 39 – 86.6 kW Class A according to EN 61000-6-4
Mechanical data	Color Air conditioning Housing material	RAL 9003, signal white For the cooling of the batteries, inverter and advertising displays; Air and liquid cooling Sheet steel
Advertising display	Size Resolution Number of monitors Remote upload of advertising content Lifetime Night mode UV resistance	75" 4K: 2160 x 3840 px 0, 1 or 2 displays Yes, the customer's content client 1,500 cd/m ² brightness after 50,000 operating hours Automatic reduction in brightness of the display depending on the measured brightness of the environment Yes, test standard: EN ISO 4892-1/-2; test class: A (artificial weathering)
User interface	Human-machine interface RFID reader Payment terminal	1x10-inch HD touchscreen, sunlight optimized HMI integrated 1x Credit and debit card reader with PIN pad for contactless payment
Service & operation	Access Operation Project specific features	Maintenance door(s), lockable Continuous operation at one location Bidirectionality; advanced communication interfaces
General data	Dimensions (L x W x H) ¹ Weight without battery modules Weight with battery modules Weight Battery module Certification Degree of protection Protection class Operating temperature range Communication channels Communication Backend protocol Charging cables Usable cable length Charging plug (vehicle interface) DC electricity meters Noise emissions	1.3x1.5 m (floor space)x 2.4 m 2.1t* 3.2t* < 25 kg CE IP54 IK10/ Payment terminal IK8, HMI unit IK8.5 -20 °C to +40 °C** 3 separate communication channels Mobile data (4G/LTE), Ethernet RJ45 10/100 Mbit/s OCPP1.6J Uncooled, external, bracket for plug 3 m CCS2 Integrated, one per charging point, each with viewing window Compliant with Eichrecht/MID For urban use

* Total weight depends on the configuration.

** Depending on configuration

¹ With charging cables, without add-on parts such as lashing eyes and without additional, specific add-on parts.

The content of this data sheet was created with utmost care. However, we shall not be held liable for the correctness, completeness and topicality with regard to the information and illustrations. We reserve the right to make modifications and illustrations may vary. All product names are trademarks and registered trademarks, and as such are the property of the respective company owning trademark rights, in each case. Editorial deadline 05/31/2023

